



Accepted / Filed

November 27, 2019

NOV 27 2019

Federal Communications Commission Office of the Secretary

Ms. Marlene H. Dortch Secretary **Federal Communications Commission** 455 12th Street, S.W. Washington, D.C. 20554

Re: FCC 302-AM Application – WRHL(AM), Rochelle, IL (FCC Facility ID # 57268)



Womble Bond Dickinson (US) LLP

1200 Nineteenth Street, NW Suite 500 Washington, DC 20036

t: 202,467,6900 202.467.6910

John F. Garziglia Partner

Direct Dial: 202-857-4455 Direct Fax: 202-261-0055

E-mail:John.Garziglia@wbd-us.com

Dear Ms. Dortch:

Submitted herewith in triplicate on behalf of Rochelle Broadcasting Company, Inc., the licensee of WRHL(AM), Rochelle, IL is an FCC Form 302-AM application submitting a proof of performance to comply with the special operating condition in the W228DT, Rochelle, IL construction permit (FCC File No. BNPFT-20171205AAU).

Should any questions arise, please contact the undersigned.

BN 21418 23 AB+ 4595 Respectfully submitted,

John F. Garziglia

Enclosures

Accepted / Filed

Federal Communications Commission Washington, D. C. 20554

Approved by OMB 3060-0627 Expires 01/31/98

NOV 27 2019 FOR FCC USE ONLY Federal Communications Commission Office of the Secretary

FCC 302-AM APPLICATION FOR AM BROADCAST STATION LICENSE

(Please read instructions before filling out form. FILE NO. BL-2019 1127 AAW				
SECTION I - APPLICANT FEE INFORMATION				
PAYOR NAME (Last, First, Middle Initial)				
Rochelle Broadcasting Company, Inc.				
MAILING ADDRESS (Line 1) (Maximum 35 characters) PO Box 177				
MAILING ADDRESS (Line 2) (Maximum 35 characters)				
CITY Rochelle	STATE OR COUNTRY (i	f foreign address)	ZIP CODE 61068	
TELEPHONE NUMBER (include area code) (815) 562-7001	CALL LETTERS WRHL	OTHER FCC IDI FCC ID 57268	ENTIFIER (If applicable)	
C. If Yes, provide the following information: Enter in Column (A) the correct Fee Type Code for the service you Fee Filling Guide." Column (B) lists the Fee Multiple applicable for the CODE (A) (B) FEE TYPE CODE O O O O	Feeable Applare applying for. Fee Type	Codes may be found tount due in Column (in the "Mass Media Services	
To be used only when you are requesting concurrent actions which re	sult in a requirement to list r	nore than one Fee Ty	pe Code.	
(A) (B) (B)	(C)	-1	FOR FCC USE ONLY	
ADD ALL AMOUNTS SHOWN IN COLUMN C, AND ENTER THE TOTAL HERE. THIS AMOUNT SHOULD EQUAL YOUR ENCLOSED REMITTANCE.	TOTAL AMOUN REMITTED WITH APPLICATION	THIS	FOR FCC USE ONLY	

SECTION II - APPLICAN	T INFORMATION				
NAME OF APPLICANT Rochelle Broadcasting Comp	pany, Inc.				
MAILING ADDRESS			-		
PO Box 177 CITY Rochelle Broadcast	ting Company Inc	STATE IL		ZIP CODE 61068	
Toolione Dioddad	ang company, mo.			01000	
2. This application is for:		Noncomn	nercial		
	AM Directional	☐ AM N	lon-Directional		
Call letters	Community of License Construc	tion Permit File No.	Modification of Construction	Expiration Date of I	
WRHL	Rochelle, IL n/a		Permit File No(s). n/a	Construction Permi n/a	I
3. Is the station naccordance with 47 C.F	ow operating pursuant to auto .R. Section 73.1620?	omatic program	test authority in	Yes Exhibit No.	No
If No, explain in an Exhi	bit.			n/a	
4. Have all the terms construction permit been	s, conditions, and obligations s n fully met?	set forth in the	above described	Yes Exhibit No.	No
If No, state exceptions in	n an Exhibit.			n/a	
the grant of the under	ges already reported, has any ca lying construction permit which d in the construction permit applie	would result in	any statement or	Yes	No
If Yes, explain in an Ex	hibit.			Exhibit No. n/a	
	ed its Ownership Report (FCC Foce with 47 C.F.R. Section 73.361		ership	Yes Does not a	No
lf No, explain in an Exhi	bit.			Exhibit No.	rr v
or administrative body was criminal proceeding, bro	ing been made or an adverse fin vith respect to the applicant or pa ought under the provisions of any elated antitrust or unfair comp nit; or discrimination?	rties to the appli law relating to t	cation in a civil or he following: any	Yes 🗸	No
If the answer is Yes, a involved, including an id (by dates and file numinformation has been required by 47 U.S.C. S of that previous submissible call letters of the st	attach as an Exhibit a full disclo- lentification of the court or admin bers), and the disposition of the earlier disclosed in connection ection 1.65(c), the applicant need sion by reference to the file numeration regarding which the applicant filling; and (ii) the disposition of	istrative body and litigation. Whe with another and only provide: (in the case station or Section	nd the proceeding the requisite application or as in a polication of an application, and application, and application.	Exhibit No.	

8. Does the applicant, or any party to the application, have the expanded band (1605-1705 kHz) or a permit or license expanded band that is held in combination (pursuant to the with the AM facility proposed to be modified herein?	either in the existing ban	nd or
If Yes, provide particulars as an Exhibit.		Exhibit No.
The APPLICANT hereby waives any claim to the use of an against the regulatory power of the United States because requests and authorization in accordance with this application amended).	e use of the same, who	ether by license or otherwise, and
The APPLICANT acknowledges that all the statements material representations and that all the exhibits are a material		
CERTIF	CATION	
 By checking Yes, the applicant certifies, that, in the case or she is not subject to a denial of federal benefits that income to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U case of a non-individual applicant (e.g., corporation, partner association), no party to the application is subject to a deincludes FCC benefits pursuant to that section. For the depurposes, see 47 C.F.R. Section 1.2002(b). I certify that the statements in this application are true, coand are made in good faith. 	ludes FCC benefits pursu S.C. Section 862, or, in ship or other unincorpora enial of federal benefits to finition of a "party" for the	ant the ited ihat ese
Name	Signature	1
Gary Petersen	les 50	Kh.
Title Prysident	Date	Telephone Number
Secretary and Treasurer	11/25/2019	(815) 562-7001
WILLFUL FALSE STATEMENTS ON THIS FORM AR (U.S. CODE, TITLE 18, SECTION 1001), AND/OR		

CONSTRUCTION

FCC NOTICE TO INDIVIDUALS REQUIRED BY THE PRIVACY ACT AND THE PAPERWORK REDUCTION ACT

The solicitation of personal information requested in this application is authorized by the Communications Act of 1934, as amended. The Commission will use the information provided in this form to determine whether grant of the application is in the public interest. In reaching that determination, or for law enforcement purposes, it may become necessary to refer personal information contained in this form to another government agency. In addition, all information provided in this form will be available for public inspection. If information requested on the form is not provided, the application may be returned without action having been taken upon it or its processing may be delayed while a request is made to provide the missing information. Your response is required to obtain the requested authorization.

Public reporting burden for this collection of information is estimated to average 639 hours and 53 minutes per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, can be sent to the Federal Communications Commission, Records Management Branch, Paperwork Reduction Project (3060-0627), Washington, D. C. 20554. Do NOT send completed forms to this address.

THE FOREGOING NOTICE IS REQUIRED BY THE PRIVACY ACT OF 1974, P.L. 93-579, DECEMBER 31, 1974, 5 U.S.C. 552a(e)(3), AND THE PAPERWORK REDUCTION ACT OF 1980, P.L. 96-511, DECEMBER 11, 1980, 44 U.S.C. 3507.

SECTION III - LI Name of Applicar		LICATION ENGIN	NEERING DATA		any Inc			
				sung Compa	arry, mic.			
PURPOSE OF A	UTHORIZATIO	ON APPLIED FOR:	(check one)					
	Station License		Direct Mea	surement of Pov	ver			
1. Facilities author	orized in const	ruction permit						
Call Sign		onstruction Permit		Hours of Oper	ation	Power in kilowatts		
WRHL	(if applicable)	n/a	^(kHz) 1060	Unlin	nited	Night 0.0)5 Da	y 0.25
2. Station locatio	n			-				
State				City or Town				
Illinois				Rochelle				
3. Transmitter lo	cation							
State	County			City or Town		Street addre		
IL	Ogle			Rochelle		(or other idea		1)
4. Main studio lo	cation							
State	County			City or Town		Street addre		
IL	Ogle			Rochelle		(or other idea 400 May Mar		1)
		n (specify only if au	thorized direction	al antenna)				
State	County	. (0,000)		City or Town		Street addre		
IL	Ogle			Rochelle		(or other identification) 400 May Mart Dr		1)
7. Does the samp	oling system m	enerating equipment neet the requirement of the description of the	nts of 47 C.F.R. S	Section 73.68?			Exhibit N	No No Applicable
8. Operating cons	stants:							١
	or antenna cu	rrent (in amperes)		RF common por modulation for	oint or antenna o day system	· ·	peres) w 2.32	ithout
operating frequen		point resistance (in	ohms) at	operating frequ	enna or common uency		nce (in of	ıms) at
Night	50	Day	50	Night	-j21.2	Day	-i2	21.2
Antenna indication	ns for direction	al operation			J =		,	
		Antenna i		Antenna mo		Anten	na base	currents
Tower	rs	Phase reading(current		Night		Day
1(W) ASRN	1009547	Night -102.6°	-102.6°	Night 0.562	Day & CH 0.562	Night		Day
2(C) ASRN		0°	0°	1.000	1.000			
3(E) ASRN		+104.2°	+104.2°	0.443	0.443			
Manufacturer and	type of antenr	na monitor:	mae Instrument	6 AM-10 (204)	c/n1263			

Potomac Instruments AM-19 (204) s/n1263

SECTION III - Page 2

9. Description of antenna system ((f directional antenna is used, the information requested below should be given for each element of the array. Use separate sheets if necessary.) If antenna is either top Type Radiator Overall height in meters of Overall height in meters Overall height in meters radiator above base loaded or sectionalized, above ground (without above ground (include Vertical steel uniform describe fully in an insulator, or above base, if obstruction lighting) obstruction lighting) cross section guyed Exhibit. grounded. insulated tower Exhibit No. 1: 68.6, 2: 69.2, 3: 68.9 67.6 1: 68.6, 2: 68.6, 3: 68.9 This is a Method of Moments Proof Shunt Excitation Geographic coordinates to nearest second. For directional antenna give coordinates of center of array. For single vertical radiator give tower location. 0 North Latitude West Longitude 30 41 55 24 89 03 If not fully described above, attach as an Exhibit further details and dimensions including any other Exhibit No. antenna mounted on tower and associated isolation circuits. Also, if necessary for a complete description, attach as an Exhibit a sketch of the details and Exhibit No. dimensions of ground system. 10. In what respect, if any, does the apparatus constructed differ from that described in the application for construction permit or in the permit? 11. Give reasons for the change in antenna or common point resistance. No change. W228DT construction permit condition #2 requires this filing. I certify that I represent the applicant in the capacity indicated below and that I have examined the foregoing statement of technical information and that it is true to the best of my knowledge and belief. Signature (check appropriate flox below) Name (Please Print or Type) Mark A. Mueller Address (include ZIP Code) November 25, 2019 Mueller Broadcast Design 613 S. La Grange Rd. Telephone No. (Include Area Code) (708) 352-2166 La Grange, IL 60525 mark@muellerbroadcastdesign.com Registered Professional Engineer **Technical Director Technical Consultant** Chief Operator

FCC 302-AM (Page 5) August 1995

Other (specify)

WRHL, ROCHELLE, ILLINOIS **DIRECTIONAL ANTENNA** PROOF OF PERFORMANCE **NOVEMBER 2019**

Exhibit EE ENGINEERING EXHIBIT TABLE OF CONTENTS

1.	Affidavit	Page 2
2.	Introduction Statement of Eligibility for 73.151(c) Processing Measurement Procedures	Page 3 Page 3 Page 4
3.	Information required by 47 CFR 73.151(c):	
	 a. Model Data b. Detuned Tower Currents c. Matrix Calculations d. Operating Tower Currents e. Tower Drive Information f. Sample System Verification g. Reference Point Field Strength Measurement h. Tower Survey 	Page 5 Page 6 Page 7 Page 8 Page 8 Page 9 Page 11 Page 12
4.	Preparer's Certification	Page 12

Rochelle Broadcasting Company, Inc. WRHL (AM), Rochelle, Illinois Directional Antenna Model Proof of Performance November 2019

Mueller Broadcast Design 613 S. La Grange Road La Grange, Illinois 60525 (708) 352-2166

State of Illinois)
)ss
County of Cook)

Mark Alan Mueller, first being duly sworn, deposes and says that he is a Broadcast Technical Consultant and owner of Mueller Broadcast Design, which has been retained by Rochelle Broadcasting Company, Inc., licensee of WRHL (AM), Rochelle, Illinois to prepare the following engineering exhibit. He is a licensed first-class radiotelephone operator, license number P1-18-44514 (renewed: PG-18-21512) and has been engaged in radio broadcast engineering work for a period of over 43 years. During this time he has been responsible for the preparation of many engineering exhibits and reports for submission to the Federal Communications Commission. He was awarded the Bachelor of Science degree from the University of Illinois at Urbana-Champaign.

The following exhibits were prepared by him and they are true and correct to the best of his knowledge and belief.

November 25, 2019

Mark A. Mueller, Affiant

Male C. Moelle

Engineering Report For Rochelle Broadcasting Company, Inc. WRHL(AM) Rochelle, Illinois November 2019

This engineering report documents the Directional Antenna Performance Verification measurements for WRHL (AM), FCC facility ID number 57268, Rochelle, Illinois. WRHL operates on 1060 KHz with 250 watts and a three tower directional antenna daytime and 50 watts using the same daytime towers and pattern at night. This Verification is for the purpose of relicensing the WRHL patterns under Method of Moments and documents the required "model proof" to update the original 1966 license filing data. This also covers the installation of the antenna and transmission line for FM translator station W228DT, FCC Facility ID number 200245 which is located on the center (#2) tower. WYOT (FM), FCC Facility ID number 57269 is co-located on the west (#1) tower. All measurements were made personally by the writer in accordance with the FCC rules at 47 CFR 73.151(c). No changes were made to the licensed patterns.

Eligibility for 73.151(c) Processing

The WRHL antenna system consists of three conventional insulated uniform cross-section triangular 14" face series-fed steel guyed towers each 67.6 meters tall, 86° at the WRHL frequency of 1060 KHz. No changes were made in the tower configuration. They are sampled at the base using Delta TCT-3 toroidal current transformers. The ground system is of standard design, consisting of 120 equally-spaced buried bare copper wire radials around each tower 70.8 meters long (90°) except for those which intersect where three-inch copper straps terminate the radial intersections. A 3" strap interconnects the towers to each other and to the phasor and transmitter. No physical changes were made to the previously licensed towers or ground system.

Measurements

The WRHL antenna system was modeled using Westberg Consulting's Phasor Professional 2.1.1 which calculates the tower matrix values as well as the proper operating parameters. The towers and sample lines were measured and documented using an Array Solutions PowerAIM-120 network analyzer serial number 1019 operated in accordance with the manufacturer's instructions. This analyzer exhibits excellent stability and field performance and since it operates "floating" via battery power and a Bluetooth radio connection to the associated computer no RF ground loop issues arise.

The three WRHL towers are identical in height and are base sampled using toroidal current transformers which are located at the output of the matching network on the lead to the tower. Each tower was disconnected at the sample transformer location and was measured at that point. The other towers were individually left floating for each measurement as required, plus additional measurements with the subject tower base insulator shorted to measure the feedline impedance with the ATU network disconnected. The only other component in circuit for these measurements was a static drain choke to ground which measures more than +j3,000 ohms at 1060 KHz, more than 60 times the highest base Z. These measurements are documented below and show excellent agreement with the Westberg theoretical numbers.

Prior to tuning the array, the Potomac Instruments AM-19(204) antenna monitor was calibrated and proper operation was verified following reinstallation using the built-in functions.

613 S. La Grange Road La Grange, Illinois 60525 (708) 352-2166

MODEL DATA:

Tower Data:

WRHL TOWER INFORMATION						
	Tower Height (°)	Spacing (°)	Orientation	Face Width (in.)	Radius (in.)	Velocity Factor
Tower 1	86.0000	0.0000	0.0000	14.0000 / 14.0000	6.4663 / 6.4663	0.890000
Tower 2	86.0000	90.0000	80.0000	14.0000 / 14.0000	6.4663 / 6.4663	0.910000
Tower 3	86.0000	180.0000	80.0000	14.0000 / 14.0000	6.4663 / 6.4663	0.917000

Measured Impedance Matrix [47 CFR 73.151(c)(1)]

WRHL MATRIX INFORMATION Other Towers Open					
	Impedance (calculated)	impedance (measured)			
Tower 1	51.55 + j59.78	50.79 +j61.52			
Tower 2	45.27 + j46.23	45.74 +j45.72			
Tower 3	46.36 + j42.58	43.78 +j44.38			

Measured data includes reactance of connection from the TCT location to the tower.

The Westberg Phasor Professional method-of-moments model fully complies with all FCC requirements for tower radius, height, segment length, and calculation reference points. No shunt capacitance was used. Towers were adjusted by varying the propagation velocity as shown above. The corrected measured impedances agree with the model within +/- 2 ohms and +/- 4%. Westberg's Phasor Professional uses a single wire of the desired effective radius divided into segments or no more than 10° electrical length each to model the tower.

DETUNED TOWER CURRENTS from Westberg Phasor Professional

	ETUNED TO	OWER	CURR	ENTS	
1	Ţ	ower	1		
0.0000	0000.0 < 0.00	00 - 86	5.00° at	ove grour	ıd
0.02224	1 > -125.138	026 -	76.44°	above gro	und
0.03431	8 > -125.664	512 -	66.89°	above gro	und
0.03864	0 > -126.269	552 -	57.33° a	above gro	und
0.03497	0 > -127.023	480 -	47.78° a	above gro	und
0.02303	3 > -128.303	194 -	38.22° a	above grou	ınd
0.00270	2 > -145.304	687 - 3	28.67° a	above grou	und
0.02674	48 > 54.7709	03 - 1	9.1 1° a	bove grou	nd
0.0656	56 > 53.282	428 - 9	9.56° at	ove groun	ıd
0.1266	98 > 52.5279	963	0.00° al	ove grou	nd
	HARRY T	ower	2		
0.0000	00 > 0.00000	00 - 86	6.00° ab	ove groun	d
0.02154	2 > -125.813	429 - 1	76.44° a	above grou	ınd
	4 > -126.308				
0.03729	8 > -126.868	114 - !	57.33° a	above grou	ınd
0.03371	3 > -127.556	862 - 4	47.78° a	above grou	ınd
0.02217	2 > -128.720	307 - 3	38.22° a	above grou	ınd
0.00254	6 > -144.484	659 - 2	28.67° a	above grou	ınd
	2 > 54.0759				
0.0633	25 > 52.731	118 - 9	.56° ab	ove groun	d
0.1223	69 > 52.0505	61(0.00° at	ove grour	ıd
	Ţ	ower:			
0.0000	00 > 0.00000	00 - 86	.00° ab	ove groun	d
	5 > 148.8003				
0.02240	7 > 149.4343	312 - 6	6.89° a	bove grou	nd
	1 > 150.0897				
0.02229	4 > 150.8695	590 - 4	7.78° a	bove grou	nd
0.01438	3 > 152.2044	163 - 3	8.22° a	bove grou	nd
	6 > 176.6158		_		
0.01753	1 > -30.9611	17 - 1	9.11° a	bove grou	nd
	38 > -29.492				
0.08047	8 > -28.7248	364(0.00° at	ove grour	nd

MATRIX CALCULATIONS from Westberg Phasor Professional

	ZMatrix	
51.55 + j59.78	24.46 - j22.03	-13.32 - j18.90
24.46 - j22.03	45.27 + j46.23	23.32 - j20.67
-13.32 - j18.90	23.32 - j20.67	46.36 + j42.58

713.32 - 110	5.30 23	.52 - 12	0.07	10.30 T J42.30	
		YMatri	X		
0.006871 - j0.007961	0.0041	20 + j0	.00409	90 0.000865 -	j0.000499
0.004120 + j0.004090	0.0060	71 - j0.	.00707	72 0.004335 +	j0.005139
0.000865 - j0.000499	0.0043	35 + j0	.00513	39 0.009299 -	j0.008984
	HMatrix	(- M =	[Н] Х	F	
0.018256 + j0.001552	0.0005	59 + j0	.00086	62 0.000627 -	j0.000278
0.000540 + j0.000829	0.0190	65 + j0	.00150	01 0.000542 +	j0.000832
0.000595 - j0.000263	0.0005	36 + j0	.00082	21 0.019349 +	j0.001482
HMat	rix-inve	erse - [FJ = [ŋ¹X[ŋ	A CONTRACTOR OF THE
54.386555 - j4.538662	-1.870	593 - j2	.14070	00 -1.644889	+ j1.195184
-1.805813 - j2.057311	52.073	414 - j3	3.8301	78 -1.685828	- j1.962171
1.560888 + j1.132386	-1.6656	558 - j1	.93589	93 51.384785	- j3.870040

TOWER OPERATING CURRENTS from Westberg Phasor Professional

Tower 1	
0.000000 > 0.000000 - 86.00° above	ground
0.331939 > -10.967764 - 76.44° abov	e ground
0.596352 > -10.367197 - 66.89° abov	e ground
0.822709 > -9.702744 - 57.33° above	ground
1.007639 > -8.938773 - 47.78° above	ground
1.146609 > -8.033844 - 38.22° above	ground
1.235250 > -6.925819 - 28.67° above	ground
1.269756 > -5.508504 - 19.11° above	ground
1.246514 > -3.576530 - 9.56° above	ground
1.139700 > 0.0000000.00° above	ground
Tower 2	
0.000000 > 0.000000 - 86.00° above	ground
0.474913 > 96.500689 - 76.44° above	e ground
0.863788 > 96.940137 - 66.89° above	e ground
1.208714 > 97.405518 - 57.33° above	e ground
1.505101 > 97.914717 - 47.78° above	e ground
1.746464 > 98.485922 - 38.22° above	e ground
1.926326 > 99.145125 - 28.67° above	ground
2.039007 > 99.934728 - 19.11° above	ground
2.079602 > 100.931564 - 9.56° above	ground
2.029290 > 102.5888930.00° abov	e ground
Tower 3	
0.000000 > 0.000000 - 86.00° above	ground
0.191446 > -156.526760 - 76.44° abov	e ground
0.350709 > -156.167027 - 66.89° abov	e ground
0.494559 > -155.817534 - 57.33° abov	e ground
0.621081 > -155.470493 - 47.78° abov	e ground
0.727558 > -155.120001 - 38.22° abov	e ground
0.811253 > -154.757224 - 28.67° abov	e ground
0.869778 > -154.367252 - 19.11° abov	e ground
0.901216 > -153.923106 - 9.56° abov	
0.901881 > -153.2559030.00° abov	e ground

TOWER DRIVE INFORMATION – DAY

	Field Ratios	Field Phase	Drive Imped. (Ω)	Gurrent	Monitor*	Power (W)
Tower 1-W	1.0000	0.0000	83.01 + j128.94	1.14 ≰ 0.00	0.562 ∡ -102.6°	107.8208
Tower 2-C	1.5300	106.0000	36.58 + j47.82	2.03 \$ 102.59	1.000 ≰ 0°	150.6325
Tower 3-E	0.6400	-148.0000	14.20 + j16.83	0.90 4 -153.26	0.443 4 +104.2°	11.5467

Note: The same parameters are used day and night.

^{* =} These are the pattern parameters used to tune the array and are on the Form 302.

613 S. La Grange Road La Grange, Illinois 60525 (708) 352-2166

Sample System Verification [47 CFR 73.151(c)(2)]

Sample Lines:

Andrew 3/8" LDF2-50J Foam Dielectric Heliax

85% velocity factor, 50 ohms +/- 1 ohm

Sample Element Type:

Delta TCT-3 Toroidal Current Transformers, 1 volt per amp into a 50

ohm load

Location:

At output of antenna tuning network on tower feedline

Operating Potential:

Grounded

Antenna Monitor:

Potomac Instruments AM-19(204), s/n 1263

TCT Phase and Ratio Test (Tower 2 is reference) and Impedances at 1060 KHz:

Tower 1 (s/n 214):

1.000/+0.2°

49.664 +j1.289 ohms

Tower 2 (s/n 220):

1.000/ 0°

49.639 +i1.605 ohms

Tower 3 (s/n 298):

0.997/ 0.0°

49.934 +i1.804 ohms

The phase and ratio calibration test was done with all transformers removed from the ACUs and configured adjacent to each other reading 1 amp of RF current into a 50 ohm dummy load. The cables used to connect the TCTs to the monitor are identical in electrical length and characteristic impedance, and are maintained by the writer for these tests.

Sample Impedance From Monitor End at 1060 KHz with TCTs connected:

Tower 1 (W) Sample Impedance:

52.654 -j1.170 ohms

Tower 2 (C) Sample Impedance:

52.895 -j0.438 ohms

Tower 3 (E) Sample Impedance:

53.271 -j2.233 ohms

Sample lines and elements were measured with the PowerAIM-120 Network Analyzer. All lines and sample elements agree within 2 ohms. The maximum variation between sample elements is 0.3% and 0.2°. The maximum variation in sample line length is 0.3°

WRHL Sample Line Length and Impedance Test:

F								
	Tower 1							
	<u>Marker</u>	Freq (MHz)	<u>Rs</u>	Xs	Zmag	Z (ohms)	Length °	Error°
	F-45°	0.986189	4.962	-50.214	50.459			
	Fc	1.060000	3.553	-26.938	27.171		241.84	0
	F@270°	1.183427	3.112	0.000	3.112		270	
	F+45°	1.380665	7.239	49.365	49.893	50.175		
		Tower 2						
	Marker	Freq (MHz)	Rs	Xs	Zmag	Z (ohms)	<u>Length</u> °	<u>Error°</u>
	F-45°	0.985424	5.184	-50.613	50.878			
	Fc	1.060000	3.478	-26.788	27.013		242.028	-0.188
	F@270°	1.182509	3.178	0.000	3.178		270	
_	F+45°	1.379594	7.186	49.851	50.366	50.621		
				Tower	13			
	Marker	Freq (MHz)	Rs	Xs	Zmag	Z (ohms)	<u>Length</u> °	Error°
	F-45°	0.986646	5.145	-50.191	50.454			
	Fc	1.060000	3.464	-27.028	27.249		241.728	0.112
	F@270°	1.183975	3.240	0.000	3.240		270	
	F+45°	1.381304	7.280	49.350	49.884	50.168		

The maximum phase error is 0.3° and the maximum impedance difference is 0.453 ohms, well within the allowed limits.

Sample lines and elements were measured with the PowerAIM-120 Network Analyzer.

WRHL Daytime Reference Field Strength Measurements [47 CFR 73.151(c)(3)]

<u>Point</u>	<u>Distance</u>	mV/m	Coordinates (NAD 84)	<u>Description</u>			
32° Tı	rue (Minima)						
1	3.58	8.90	41.9500865, -89.0347195	Dement Rd.			
2	6.08	3.75	41.9746536, -89.0141416	100' east of 17202 Lind Rd.			
3	8.92	2.40	41.9907915, -89.0005804	Mulford Rd. 200' north of creek			
65° Tı	rue (Minima)						
1	5.24	1.20	41.9426536, -89.0003229	5543 Mulford Rd.			
2	7.05	1.30	41.9495419, -88.9805389	Towmbly Rd. 50' east of			
				Chamberlain Rd.			
3	8.89	0.90	41.9564934, -88.9604545	Woodlawn at north end of guardrail			
95° Tı	rue (Minima)						
1	3.44	3.30	41.9200934, -89.0163303	200' west of 17234 Creston Rd.			
2	4.79	4.00	41.9189556, -89.0001083	Mulford Rd. 200' south of Creston Rd.			
3	6.41	2.35	41.9176735, -88.9806676	Locust Rd.			
128° T	rue (Minima)						
1	5.97	2.70	41.8895891, -89.0009237	Paw Paw Rd.			
2	6.93	1.90	41.8842818, -88.9918256	Hayes Rd.			
3	8.04	1.25	41.8781241, -88.9812899	Locust Rd. 100' north of phone pedestal			
	rue (Maxima)	-					
1	1.24	198	41.9207785, -89.0723992	209 10 th St.			
2	1.45	178	41.9204620, -89.0748078	201 12 th St.			
3	1.76	140	41.9199692, -89.0784824	15th St. across from NB stop sign			

WRHL operates with 50 watts at night using the same directional antenna parameters so a separate nighttime table is not included.

All readings taken November 24, 2019 by Mark A. Mueller using his FIM-41, s/n 1655 last calibrated 7/16/2017.

Tower Survey [47 CFR 73.151(c)(1)(ix)]

This application coverts the WRHL license from a standard measured radial proof to Method of Moments with no other changes to the licensed directional patterns. Therefore, per §73.151(c)(1)(ix) no tower survey is required.

Preparer's Certification

This engineering report was prepared by me from data personally collected on site using equipment owned and maintained by me for this purpose. It is true and correct to the best of my knowledge and belief. The WRHL antenna system is properly adjusted as documented herein and it is requested that the WRHL license be modified to specify the operating parameters shown on the associated FCC form 302-AM.

November 25, 2019

Mark A. Mueller